

# SST™ Cold Spray Systems

## **Practical Cold Spray Coatings**

### The SST Series EP High Pressure Cold Spray System

The SST Series EP is an enhanced version of the Series P designed to Cold Spray at higher pressures. The Series EP includes a transportable cabinet, HMI controls, pressurized feeder and robotic spray gun. Depending on the application, its enhanced operating features enable users to Cold Spray harder materials at higher deposition rates and/or higher deposition efficiency than the Series P. This makes the Series EP an ideal choice for more challenging cold spray application needs.

### The Series EP system offers:

- · the ability to cold spray harder materials
- · higher coating deposition rates
- higher deposition efficiency
- · greater bond strengths
- compatibility with UltiFlow™ and UltiLife™ nozzles
- an optional Calibration Kit to calibrate the SST equipment temperature and pressure controls
- low investment cost, flexibility, and a small equipment footprint
- · ability to be integrated into automation and turnkey systems

#### **Powders**

Operating at pressures between 7 and 35 bar (100 - 500 psi), the Series EP Cold Spray system can spray standard SST powders and powder blends PLUS the following materials:


- Aluminum Alloys (AA7075, AA6061, AA4047, AA5083, AA2024, etc.)
- Ni and Ni Allovs
- Stainless Steels (304, 316)
- Ti and Ti Alloys (Ti-6Al-4V)
- Tantalum


- Niobium
- Invar
- MCrAlY
- Inconel (IN718, IN625)
- WC-Co
- Molybdenum

### Technical Specifications:

*		
	Control Unit	Spray Gun
Pressure Range	100-500 psi (7-35 bar)	
Temperature Range	25-550 °C (77-1022 °F)	
Weight	78 kg (173 lb)	21 kg (48 lb)
Dimensions	68.58 cm x 55.88 cm x 111.76 cm (27" W x 22" D x 44" H)	35.56 cm x 13.97 cm x 76.20 cm (14" W x 5.5" D x 30" H)
Power Requirements	480 V - 3Phase - 25 Amps	

#### Magnified Coating Cross-section Examples:





Titanium (SST-T5001)

SS 316 (SST-S5002)

### Contact SST today to discuss your metal coating needs.



www.supersonicspray.com

CenterLine (Windsor) Limited Supersonic Spray Technologies Division 655 Morton Dr., Windsor, ON N9J 3T9 Toll free: 800-268-8330, Tel: 519-734-8330 email: info@cntrline.com